

Low Power Camera--QG15			
Product image		Product features	
		<ul style="list-style-type: none"> ★ 4G connection ★ Remote active wake-up, two-way voice intercom ★ Quick start, start recording within 400ms ★ Intelligent detection of human movement, real-time alarm push ★ 12000mAh battery, low battery reminder 21700×3 ★ Low power system optimization ★ Free cloud storage: 1-day loop recording(China), 3-day loop recording(Overseas) ★ Three real-time recording channels, guarding multiple directions ★ Lens linkage - for close up and distant views ★ Dual light source, full color day and night ★ Low power consumption, corded electric compatible design 	
		No.	Sorts
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors viewing at the same time.
2	Collection	APP	O-KAM Pro
		CPU	T23
		Memory	1GB
		Image sensor	GC2083+GC2083+GC2083
		Minimum illumination	0.8Lux/F1.4(Color mode), 0.3Lux/F1.4 (B&W mode)
		Lens	Panorama camera: focal length 4mm, 1G3P; Tracking camera: focal length 4mm+12mm, 1G3P
		Sensor performance	Supports automatic white balance, automatic gain control, and automatic backlight compensation.
		PTZ	Horizontal 305°, Vertical 90°
3	Video	Viewing angle	Panorama camera: 100° Diagonal Tracking camera: 100° Diagonal
		Night Vision	Color night vision, dual light source, 6 dual color lights
		Compression standard	H.264 / MJPEF / JPEG
		Data rate	Main stream : 1080P/15fps Sub stream : 360P/15fps
		IR control	When the IR night vision function is enabled, IR and ICR are automatically detected; when the IR night vision function is disabled, IR is off and ICR is fixed in the day vision mode.
		Bit rate	CBR/VBR two rate control modes, with an output rate range of 128 to 4096kbps.
4	Audio	Image adjustment	Brightness, contrast, vertical, horizontal adjustable, OSD display.
		Input	Built-in-38dB microphone
		Output	Built-in 8Ω2W speaker
		Sampling frequency/bit width	8KHz/16bit
5	AI	Compression standard/Bit Rate	G711A
		Humanoid detection	Humanoid detection, filtering invalid alarm events.
		Area detection	Customize detection zones, only monitor areas that matter.
		Intelligent notification sound	Set different notification sounds for different devices, so that you can accurately determine which device is triggered.
		Intelligent alarm sound	Set different alarm sounds based on different scenarios.
6	Network	More AI functions (under testing)	Pets, vehicles, packages, etc
		Wireless connection	Scan the device QR code to add/scan the APP QR code
		China Cat1	FDD:B1/B3/B5/B8 TDD:B34/B38/B39/B40/B41
7	Key	Overseas Cat4	European/Japanese/American/Australian versions
		Key 1	On/Off
8	Storage	Reset key	Long press to restore factory settings
		Micro SD card	Supports Micro SD card (up to 256GB)
9	Alarm	Cloud storage	Free cloud storage: 1-day loop recording(China), 3-day loop recording(Overseas)
		Sound light alarm	Sound and light alarm, 6 infrared lights+6 white lights, full-color night vision
10	Physical Indicators	Alarm detection	Supports PIR human movement detection, detection range 10 meters
		Rated voltage	DC5V±5%
		Power supply	Built in 12000mAh battery, 3*21700
		Power consumption	Sleep standby 300uA, working: 400MA-1.5A max
		Operating condition	Temperature: -10 ~ 55°C; Humidity: < 90%
		Weight	Gross weight: (Note: in kind prevail)
		Size	
		What's in the box	Camera*1, MICRO TYPE-C*1, manual*1, (optional solar panel * 1 and solar panel bracket * 1)