

Shenzhen VeePai IOT Intelligent Technology Co., Ltd B302, Shanshui Building, Nanshan Yungu Innovation Industrial Park, 1183 Liuxian Blvd, Nanshan District, Shenzhen, China http://www.veepai.com

Low Power Indoor PTZ CameraQW5-2Y			
	Pre	oduct Image	Product features
			★Wireless connection
			★Remote active wake-up,two-way voice intercom
			★ Quick start, start recording within 400ms
			★Intelligent detection of human movement, real-time alarm push
			★5000mAh battery, low battery reminder ,18650×2
		13	★Low power system optimization
			*Free cloud storage: 1-day loop recording(China), 3-day loop recording(Overseas)
	•	•	*Tree croud storage. 1-day 1000 recording (china), 5-day 1000 recording (overseas) *Dual light source, full color day and night
			★Low power consumption, corded electric compatible design
No.	Sorts	Туре	Parameters
		Operating system	Linux
1	System	Online visitor	Supports 4 visitors viewing at the same time.
		APP CPU	O-KAM Pro
2	Collection		T23
		Memory	512Mb
		Image sensor Minimum illumination	GC2083+GC2083,1/3 CMOS
2		Lens	0.8Lux/F1.4(Color mode),0.3Lux/F1.4 (B&W mode)
		Sensor performance	Standard lens 14mm
		,	Supports automatic white balance, automatic gain control, and automatic backlight compensation.
		Viewing angle	D100° diagonal Color night vision, dual light source, tracking camera (2 infrared lights+2 white lights), panorama camera (2 infrared lights+2)
		Night Vision	white lights)
		Compression standard	H.264 /MJPEF/JPEG
		Data rate	Main stream: 1296P/15fps, sub stream: 360P/15fps
3	Video		When the IR night vision function is enabled, IR and ICR are automatically detected; when the IR night vision function is
		IR control	disabled, IR is off and ICR is fixed in the day vision mode.
		Bit rate	CBR/VBR two rate control modes, with an output rate range of 128 to 4096kbps.
		Image adjustment	Brightness, contrast, vertical, horizontal adjustable, OSD display.
		Input	Built-in-38dB microphone
4	Audio	Output	Built-in 8Ω1W speaker
4		Sampling frequency/bit width	8KHz/16bit
		Compression standard/Bit Rate	G711A
	Al	Humanoid detection	Humanoid detection, filtering invalid alarm events.
5		Area detection	Customize detection zones, only monitor areas that matter.
		Intelligent notification sound	Set different notification sounds for different devices, so that you can accurately determine which device is triggered.
		Intelligent alarm sound	Set different alarm sounds based on different scenarios.
		More Al functions	Pets, vehicles, packages, etc
		(under testing)	
5	Network	Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P,IPV4 etc.
		Wireless network	IEEE802.11b/g/n
		Wireless frequency	2.4~2.4835GHz
		Wireless security encryption	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
		Wireless connection method	AP hotspot, Scan QR code, Bluetooth
6	Key	Key 1	On/Off
		Reset key Rotation angle	Long press to restore factory settings Horizontal 301 °, vertical 70 °
7	PTZ	Presets	
		Cruise function	Supports customizing 5 preset positions Horizontal cruise, vertical cruise, preset cruise (stops automatically after 10 minutes)
		Physical privacy	Supports
		External TF card	Supports Supports T-Flash cards (up to 256GB)
	Storage	Cloud storage	Free cloud storage: 1-day loop recording(China), 3-day loop recording(Overseas)
9	Alarm	Detection	Supports PIR infrared human detection
		Charging voltage	DCSV±5%
		Power supply	Built in 5000mAh battery, 2*18650
		P.P. /	
		Power consumption	
10	Physical Indicators	Power consumption Operating condition	Sleep current 300uA, working: 230mA Temperature: -10 ~ 55°C: Humidity: < 90%
10	Physical Indicators	Operating condition	Temperature: -10 ~ 55°C; Humidity: <90%
10	Physical Indicators	Operating condition Weight	Temperature: -10 ~ 55°C; Humidity: < 90% Gross weight: (Note: in kind prevail)
10	Physical Indicators	Operating condition	Temperature: -10 ~ 55°C; Humidity: <90%