

Shenzhen VeePai IOT Intelligent Technology Co., Ltd B302, Shanshui Building, Nanshan Yungu Innovation Industrial Park, 1183 Liuxian Blvd, Nanshan District, Shenzhen, China http://www.veepai.com

QC3			
Product Image			Product features
Ŕ			★ Wireless connection
			★ Full duplex two-way audio
			★ Hidden interface design
			★ Worldwide cloud storage service
			★ Small and compact appearance
			★ 1296P UHD
			★ Universal motherboard, supports 90% housing
••			
No.	Sorts	Туре	Parameters
	System	Operating system	Linux
1		Online visitor	Supports 4 visitors viewing at the same time.
		APP	O-KAM Pro
	Collection	CPU	T23
2		Memory Image sensor	512Mb
		Minimum illumination	GC2083, 1/3 CMOS
		Lens	0.8Lux/F1.4(Color mode),0.3Lux/F1.4 (B&W mode) Standard lens 14mm, 1G3P, focal length 4mm IR-CUT integrated
		Sensor performance	Supports automatic white balance, automatic gain control, and automatic backlight compensation.
		Shutter type	Electronic rolling shutter
		Viewing angle	Diagonal 100 °
		Night Vision	Color night vision, dual light sources, visible distance: 10~20 meters
	Video	Compression standard	H.264 /MJPEF/JPEG
3		Data rate	Main stream: 1296P/15fps, sub stream: 360P/15fps
			When the IR night vision function is enabled, IR and ICR are automatically detected; when the IR night vision function
		IR control	is disabled, IR is off and ICR is fixed in the day vision mode.
		Bit rate	CBR/VBR two rate control modes, with an output rate range of 128 to 4096kbps.
		Image adjustment	Brightness, contrast, vertical, horizontal adjustable, OSD display.
		Input	Built-in-38dB microphone
4	Audio	Output	Built-in 8Ω1W speaker
		Sampling frequency/bit width	8KHz/16bit
		Compression standard/Bit Rate	G711A
	AI	Humanoid detection	Humanoid detection, filtering invalid alarm events.
		Human tracking	When it detects human figure, it will frame and track
		Area detection	Only monitor areas that matter.
5		Intelligent notification sound	Set different notification sounds for different devices, so that you can accurately determine which device is triggered.
		Intelligent alarm sound	Set different alarm sounds based on different scenarios.
		More AI functions	Pets, vehicles, packages, etc
		(under testing)	
6	Network	Network protocol	TCP/IP,HTTP,UDP,DHCP,DNS,NTP,RTSP,P2P,IPV4,IPV6 third party access protocols, etc
		Wireless network	IEEE802.11b/g/n
		Wireless frequency	2.4~2.4835GHz. 5.8G dual band optional
		Wireless security encryption Wireless connection method	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption AP hotspot, Scan QR code, Bluetooth
		Key	Ar hotspot, scall ok code, sidetooth
7	Key Storage	Reset key	/ Long press to restore factory settings
		Indicator light	Dual color indicator lights together with voice prompt
		Micro SD card	Supports Micro SD card (up to 256GB)
		Cloud storage	7 day cloud storage plan with 1-day loop recording
9	Alarm	Sound light alarm	Supports
		Alarm detection	Motion detection alarm, humanoid detection alarm
10	Physical Indicators	Rated voltage	DC5V. 1.5A
		Power supply	TYP-C 5V/1.5A power supply
		Operating condition	Temperature: -10 ~ 55°C; Humidity: < 90%
		Weight	Gross weight: (Note: in kind prevail)
		Size	
		Packaging list	Camera*1, TYP-C*1, manual*1, 5V1.5A-TYP-C adapter
	•		· · ·