




Shenzhen VeePai IOT Intelligent Technology Co., Ltd  
B302, Shanshui Building, Nanshan Yungu Innovation Industrial Park, 1183 Liuxian Blvd, Nanshan District, Shenzhen, China  
<http://www.veepai.com>

Traditional NVR -- NQ10			
Product image			Product features
			★Through cloud service, remote monitoring can be achieved in one step.
			★Standard Onvif protocol, can be connected to IPCs that support Onvif protocol
			★Support P2P cloud platform remote monitoring, realize APP instant preview + remote video playback
			★Compatible with a wide range of shells, supporting 95% of the shells on the market
			★The most user-friendly, popular, commercial 10-ch embedded H.265 NVR
			★Integrated board design for more convenient assembly
			★4K Ultra HD
			★Can be connected to high-definition network cameras. Provides preview/recording/playback functions
No.	Sorts	Type	Parameters
1	System	CPU	A1
		Memory	
		Video format	H264/H265
		Operating System	Embedded Linux
2	Video	IP Video Input	10-ch, supports up to 10* IPC video input
		Preview	Main stream fps; Sub stream fps
		Recording	10 * / fps
		Playback	1*4K / 4*5MP
		VGA Output	Resolution supported: 1920×1080, 1440×900, 1280×1024, 1280×820, 1024×768
		HDMI Output	Resolution supported: 3840*2160, 2560×1440, 1920×1080, 1440×900, 1280×1024, 1280×820, 1024×768
3	Audio	Input	Support
		Output	Support
		Two Way Audio	Not support
4	Recording	Recording Resolution	Supports 720P/960P/1080P/3MP/4MP/5MP/8MP
		Real Time Recording Channel	10-ch
5	Playback	Recording Mode	Scheduled recording, intelligent event recording, custom recording
		Synchronous Playback	4 channels playback (main stream)
		Search Mode	Search by time point, calendar, event, channel
6	Backup	Smart Playback	Supports motion and humanoid events, and can directly locate events
		USB Portable Hard Drive, USB Flash Drive	Support
7	Network	Backup File Format	
		Network Protocol	TCP/IP,IPv4,DHCP,RTSP,ONVIF,P2P etc.
8	Storage	Network Interface	1 RJ45 interface, 10/100M adaptive
		HDD	1个SATA interface (Up to 14TB capacity for each disk)
		Recording Event	Scheduled recording, mobile detection linkage recording, and human detection linkage recording
9	Remote Access	Cloud Storage	/
		Browser	/
		Client	/
10	Others	Mobile Operating System	Android, IOS
		External Interface	2*USB2.0 interface(Rear); Support mouse, USB upgrade, import and export
		Front Panel	Supports power interface, recording, alarm( 3 status indicator light)
11	Physical Indicators	Rated voltage	DC12V / 2A
		Power supply	12V plug in power supply
		Operating condition	Temperature: -10 ~ 55°C; Humidity: < 90%
		Weight	Gross weight: (Note: in kind prevail)
		Size	(Note: in kind prevail)
		Packaging list	Camera*1, manual*1, DC12V 2A (optional according to the motherboard)